



Accessories for Conductivity Measurement



Connection cable

Connection cable A

for 2- and 4-electrode cells at UNICON-LF field case with 8 pole cable socket and 8 pole cable plug, brass plated, PU-cable

Ordering No.	length [m]	protection class
SKM8-02	2	IP67
SKM8-05	5	IP67
as before, but plug SS-type, PVC cable		
SKM8-02-VA	2	IP67
SKM8-05-VA	5	IP67

Connection cable B

for 2-electrode-cells at UNICON-LF field case with 4 pole angle entry socket acc. to DIN EN 175301-803/A and 8 pole cable plug brass plated, PU-cable

Ordering No.	length [m]	protection class
SKM4B-02	2	IP65
SKM4B-05	5	IP65
as before, but plug SS-type, PVC cable		
SKM4B-02-VA	2	IP65
SKM4B-05-VA	5	IP65

Connection cable D

for 2- and 4-electrode-cells at LF1010/LF9648 with 8 pole cable socket brass plated and 6 pole pigtail, PU-cable

Ordering No.	length [m]	protection class
SKM8E-02	2	IP67
SKM8E-05	5	IP67
SKM8E-10	10	IP67
SKM8E-25	25	IP67
as before, but plug SS-type, PVC cable		
SKM8E-02-VA	2	IP67
SKM8E-05-VA	5	IP67
SKM8E-10-VA	10	IP67
SKM8E-25-VA	25	IP67

Connection cable E

for 2-electrode-cells at LF1010/LF9648 with 4 pole angle entry socket DIN EN 175301-803/A and 6 pole pigtail, PU-cable

Ordering No.	length [m]	protection class
SKM4E-02	2	IP65
SKM4E-05	5	IP65
SKM4E-10	10	IP65
SKM4E-25	25	IP65

Calibration accessories

Reference solution for calibration (250 ml)

Ordering No.	Conductivity [mS/cm] at 25°C
REF-LF-0001	0.147
REF-LF-0010	1.413
REF-LF-0100	12.88
REF-LF-1000	111.8

Reference solution for calibration acc. to USP <645>, (1000 ml)

Ordering No.	Conductivity [µS/cm] at 25°C
EC15	15,0

Precision-thermometer

Ordering No.	Measuring range °C
N63802	17.0..35.0 scale solution 0.05 °C accuracy ±0.1 °C

