

Grain moisture measuring equipment

Data sheet

FS4

Whole corn measurement with a proven sample quantity of 300 g and sample temperature measurement for agriculture, dealers, research, lab and food industry.

Qualities:

- very fast and accurate proven measurement by measuring 300 g of the whole corn
- for all kinds of corn
- custom-made calibration for special fruits
- reduces drying costs
- protection against fungus and further sequence damage
- automatic self calibration
- integrated data storage
- printer connection
- on-line function for data transportation
- reference- and customer calibration line
- Svery easy service
- large, lighted LCD screen
- menu language in German, English, Italian, French

Maize, rye, triticale, wheat, dinkel wheat, barley, oat, colesseed, peas, soy beans, sun flowers, rice etc.



Description:

Only a accurate moisture measurement of grain and special fruits makes a fair settlement possible for manufacturers, dealers and end users.

That's why quality control gets more important. Production problems will be eliminated, and water will not be bought against high cost prices.

With this gain moisture measuring device a measurement will be supported within seconds.

Apply the measuring device, fill the measuring chamber with grain and

read the moisture content on the LCD display.

The measuring data can be stored in the device

The measuring values can be stored inside the device or transmitted to a PC or printer

ACO
Automation
Components

moisture measuring

technical data

| | |
|----------------------------------|---|
| Resolution | 0,1% |
| Measuring range | 5% to 50% (depends on kind of grain) |
| Sample temperature measurement | hectoliter compensated |
| Display | LCD lighted |
| Temperature | selectable to °C or °F |
| Temperature compensation | automatized |
| Measuring results within seconds | |
| Sample preparation | not necessary |
| Hold-funktion | manueller Messwertspeicher für 10.000 Werte mit Messortbeschreibung |
| Online-Function | integrated |
| Supplier-storage possibilities | integrated |
| Custom calibration | for special fruits, granulate etc. |
| Robust housing | rust-proof |
| Delivery package | digital scale, measure cup, batteries, PC-interface, case |
| Optional | printer, ISO control device guard |



ACO Automation Components
Johannes Mergl e.K.
Industriestraße 2
D-79793 Wutöschingen-Horheim
Tel. +49 (0) 7746 913 16
Fax +49 (0) 7746 913 17

www.acoweb.de
info@acoweb.de

ACO
Automation
Components

PRC Technologies Corp., Ltd.
Tel. 02 530 1714,530 1619,530 1621
Fax 02 530 1731
info@prctechnologies.co.th